



Planar® T* 3,5/100 CFi



H A S S E L B L A D

The **Planar® T* 3,5/100 CFi** lens is a very special lens. It is not just a standard **Planar®** lens with 25% more focal length. It is optimized to deliver virtually zero distortion and at the same time extremely well defined image details – sharpness – over the entire frame, and all this even at full aperture. A lens with this quality could only be developed with Carl Zeiss' extensive experience in microdocumentation and aerial mapping and surveying. So the **Planar® T* 3,5/100 CFi** lens is the first choice in optics for all photographers who combine a Hasselblad camera and a recent high resolution film for demanding aerial photography with its fast shutter speeds and hence wide open apertures. The **Planar® T* 3,5/100 CFi** lens is also an indispensable tool for all applications which require an exact reproduction of the geometry of the subject. It is, therefore, recommended as a standard optical tool for photography where the demands for detail

recognition from corner to corner are extremely high, such as architectural work, aerial surveying, documentation, industrial and scientific photography. For reproducing valuable paintings and similar artwork with sizes larger than one square meter, the **Planar® T* 3,5/100 CFi** lens should be the no. 1 lens choice. (For artwork sizes smaller than one square meter, the Carl Zeiss **Makro-Planar® T* 4/120 CFi** lens is the lens of choice.) Every Hasselblad photographer who is really serious about sharpness can't do without this lens! Preferred use: architecture, documentation, and reproduction with no distortion, large products with important small details, general industrial, aerials shot wide open, digital photography

Cat. No. of lens	10 22 17		
Number of elements	5	Close limit field size	380 mm x 380 mm
Number of groups	4	Max. scale	1 : 6.9
Max. aperture	f/3.5	Entrance pupil	
Focal length	101.3 mm	Position	37.7 mm behind the first lens vertex
Negative size	55 x 55 mm	Diameter	28.9 mm
Angular field	width 31°, height 31°, diagonal 42°	Exit pupil	
Min. aperture	22	Position	40.2 mm in front of the last lens vertex
Camera mount	CFi	Diameter	32.8 mm
Shutter	Prontor CFi 1s-1/500s, b, f	Position of principal planes	
Filter connection	bayonett series 60	H	48.9 mm behind the first lens vertex
Focusing range	infinity to 0.9 m	H'	27.6 mm in front of the last lens vertex
Working distance (between mechanical front end of lens and subject)	0.7 m	Back focal distance	73.7 mm
		Distance between first and last lens vertex	58.7 mm
		Weight	600 g



Performance data:

Planar[®] T* 3,5/100 CFi

Cat. No. 10 22 17

1. MTF Diagrams

The image height u - calculated from the image center - is entered in mm on the horizontal axis of the graph. The modulation transfer T (MTF = Modulation Transfer Factor) is entered on the vertical axis. Parameters of the graph are the spatial frequencies R in cycles (line pairs) per mm given at the top of this page.

The lowest spatial frequency corresponds to the upper pair of curves, the highest spatial frequency to the lower pair. Above each graph, the f-number k is given for which the measurement was made. "White" light means that the measurement was made with a subject illumination having the approximate spectral distribution of daylight. Unless otherwise indicated, the performance data refer to large object distances, for which normal photographic lenses are primarily used.





2. Relative illuminance

In this diagram the horizontal axis gives the image height u in mm and the vertical axis the relative illuminance E , both for full aperture and a moderately stopped-down lens. The values for E are determined taking into account vignetting and natural light decrease.

3. Distortion

Here again the image height u is entered on the horizontal axis in mm. The vertical axis gives the distortion V in % of the relevant image height. A positive value for V means that the actual image point is further from the image center than with perfectly distortion-free imaging (pincushion distortion); a negative V indicates barrel distortion.

Modulation transfer T as a function of image height u . Slit orientation: tangential — — — sagittal ———
White light. Spatial frequencies $R = 10, 20$ and 40 cycles/mm



Subject to change.
Printed in Germany 29.05.2000



Carl Zeiss
Photoobjektive
D-73446 Oberkochen
Telephone (07364) 20-6175
Fax (07364) 20-4045
eMail: photo@zeiss.de
http://www.zeiss.de